


Data Sheet

Type Number 317
Designation IEC SR 62
System Silver oxide / Zinc /
NaOH - Electrolyte



Nominal Voltage 1,55 V
Typical Capacity C 12 mAh
Load 68,1 kOhm, at 20°C down to 1.3 V

Weight (approx.) 0,18 g
Volume 0,04 ccm
Coding..... Date of Manufacturing
Month/Year

Temperature Ranges	min	max.
Storage	-10°C	65°C
Discharge	-10°C	65°C

Dimensions	min	max.
Diameter (Ø).....	5,7	5,8
Height (A/B)	1,5	1,6

Segment Watch

Main Applications Watch
Electronic

Typical Capacities (at 20°C)

Discharge Type	Load	End Voltage:	1.3 V
Continuous	68100 Ω	Time:	530 h
24h/d, 7d/w		Capacity [mAh]:	12
Current [µA]:	23	Energy [mWh]:	19

All Data contained herein is for single cells

For battery applications, performance data may vary from single cell data, depending on specific battery configuration

VARTA Microbattery GmbH, Daimlerstr. 1, D-73479 Ellwangen/Jagst
Tel.: (+49) 7961/921-0, Telefax: (+49) 7961/921-553

Subject to change without prior notice!
Date of issue: 2004-12-17